

Visqueen Zedex Housing Grade DPC

- Out-performs all other housing grade flexible DPCs
- Improved Damp Proofing Properties: strength, adhesion & water impermeability
- Improved Toughness - avoids installation damage and is easier to install
- Contains no pitch, bitumen or PVC
- BBA Accreditation 94/3059

Description

Zedex Housing Grade DPC is based on the same polymer technology as Zedex CPT High Performance DPC, the new generation material designed to give higher levels of security and integrity.

Application

Applications

Zedex Housing Grade DPC is suitable for use as a DPC in domestic and residential construction in vertical, stepped and horizontal applications. For other applications use Zedex CPT High Performance DPC. Zedex Housing Grade DPC may be used in conjunction with beam and block flooring. Installed in accordance with our instructions Zedex Housing Grade DPC provides an effective barrier against the passage of moisture and forms an effective waterproof seal.

Storage & Handling

The materials used in Zedex Housing Grade DPC are chemically stable and inert and are free of both solvents and aggressive chemicals. Zedex Housing Grade DPC is also clean and safe to use and contains no volatiles to 'leach' out. Due to its robust nature, Zedex Housing Grade DPC requires no special conditions for storage, transport, handling, usage or disposal.

Availability

Zedex Housing Grade DPC is available from selected Builders Merchants throughout the UK and through Visqueen Building Products's international network. Details of your nearest stockist can be obtained from the Technical Help Line

Technical Help Line

Visqueen Building Products offer a responsive technical service and can provide advice on any aspect of damp proofing within construction including product selection and suitability, installation advice, design assistance and product availability.

Technical Help Line:

t: 01685 840672

e: enquiries@visqueenbuilding.co.uk

Zedex High Performance Damp Proofing System

Zedex Housing Grade DPC is just one product from the Zedex High Performance Damp Proofing System;

- Zedex CPT High Performance DPC
- Zedex Pre-Formed Cavity Trays
- Zedex Jointing System

Installation

Guidelines

Installation must be in accordance with BS5628-3: 1985, BS8000-3:1989, BS8215:1991, BRE Digest 380 Damp Proof Course and the procedures set out in BBA 94/3059 Detail Sheet 3.

Zedex Housing Grade DPC must extend through the full thickness of the wall, including pointing, applied rendering or other facing materials. Zedex Housing Grade DPC must be laid on a wet, even bed of mortar, and perforations in adjacent courses of brickwork must be completely filled with mortar. Zedex Housing Grade DPC must not be damaged by cavity cleaning after installation. All laps in Zedex Housing Grade DPC must be a minimum of 100mm and sealed using Zedex Jointing Tape. (For further information refer to the BBA Certificate (94/3059) or to the Zedex DPC Application Guide.

t. 01685 840672

f. 01685 842580

enquiries@visqueenbuilding.co.uk

www.visqueenbuilding.co.uk

Document last updated: 23/06/2005

VISQUEEN
BUILDING PRODUCTS

Visqueen Zedex Housing Grade DPC

Typical Properties	
Tensile Strength	20.4 N/mm ²
Elongation at Break	515 %
Tear Strength	135 N/mm ²
Water Vapour Permeability	0.3 g/m ² /day
Nominal Thickness	0.6 mm
Nominal Weight	0.6 kg/m ²
Roll Length	20m
Roll Width	100mm to 1500mm