

# Visqueen Zedex CPT High Performance DPC

- Zedex CPT High Performance DPC out performs all other high performance flexible DPCs.
- Contains no pitch, bitumen or PVC.
- Made of modern Co-Polymer Thermoplastic (CPT), it is safe, clean to handle and inert.
- Retains it's properties providing long term stability - contains no volatiles to leach out.
- Used throughout the UK, has BBA Accreditation, is backed by a full technical support service and includes a range of Pre-Formed Cavity Tray Units and a Jointing System.

## Description

Zedex CPT High Performance DPC is a new generation of damp proof course. Made from Co-Polymer Thermoplastic (CPT), it possesses the characteristics necessary for it to perform effectively under harsh conditions.

Zedex CPT High Performance DPC provides superior strength, adhesion and water impermeability properties. Improved toughness helps to avoid damage during installation and is compatible with other Visqueen products.

## Application

### Typical Properties

The anti-ageing and dimensional stability properties, as well as it's resistance to rot, damage, damp conditions, mildew and UV light ensure that Zedex CPT High Performance DPC is untroubled by environmental conditions over time. Zedex CPT High Performance DPC will continue to perform at a high level for the lifetime of the building.

### Applications

Zedex CPT High Performance DPC is suitable for use as a DPC in all types of building construction and can be used in vertical, horizontal, stepped and cavity tray applications. Zedex CPT High Performance DPC provides an effective barrier against the passage of moisture and forms an effective waterproof seal.

### Storage & Handling

The materials used in Zedex CPT High Performance DPC are chemically stable and inert and are free of both solvents and aggressive chemicals. Zedex CPT High Performance DPC is also clean and safe to use and contains no volatiles to 'leach' out. Due to it's robust nature, Zedex CPT High Performance DPC requires no special conditions for storage, transport, handling, usage or disposal.

### Availability

Zedex CPT High Performance DPC is available from selected Builders Merchants throughout the UK and through Visqueen Building Products's international network. Details of your nearest stockist can be obtained from the Technical Help Line

### Technical Help Line

Visqueen Building Products offer a responsive technical service and can provide advice on any aspect of damp proofing within construction including product selection and suitability, installation advice, design assistance and product availability.

Technical Help Line:

t: 01685 840672

e: [enquiries@visqueenbuilding.co.uk](mailto:enquiries@visqueenbuilding.co.uk)

### Zedex High Performance Damp Proofing System

Zedex CPT High Performance DPC is just one product from the Zedex high Performance Damp Proofing System;

- Zedex CPT High Performance DPC
- Zedex Pre-Formed Cavity Trays
- Zedex Jointing System

# Visqueen Zedex CPT High Performance DPC

## Installation

### Guidelines

Zedex CPT High Performance DPC must extend through the full thickness of the wall, including pointing, applied rendering or other facing materials. Zedex CPT High Performance DPC must be laid on a wet, even bed of mortar, and perforations in adjacent courses of brickwork must be completely filled with mortar. Zedex CPT High Performance DPC must not be damaged by cavity cleaning after installation (For further information refer to the BBA Certificate (94/3059) or to the Zedex DPC Application Guide.

Typical Properties	
Visqueen Zedex CPT High Performance DPC	
Tensile Strength	20.5 N/mm <sup>2</sup>
Elongation at Break	539%
Tear Strength	175.0 N/mm <sup>2</sup>
Water Vapour Permeability	0.21 g/m <sup>2</sup> /day
Accelerated Weathering	
Tensile Strength.	18.9 N/mm <sup>2</sup>
Elongation at Break.	462%
Roll Dimensions	
Nominal Thickness	0.8mm
Nominal Weight	0.75 kg/m <sup>2</sup>
Roll Length	20m
Roll Width	100mm to 1500mm