

Fire Rated Expanding Foam



There are two main types of fire-rated foams available on the market today, one of which gives a fire rating for the 'surface spread of flame' only and one which offers a full 'penetration seal' for compartment walls. We are aware that to the layman this means little however to the occupant of a building during a fully developed fire the difference becomes very apparent. As the use of these products tends to be around the perimeter of door frames or sealing services penetrating a compartment wall, this full penetration product is the one to use.

Applications include:

- ✓ Sealing around door frames and screens
- ✓ Backfilling around non combustible service penetrations
- ✓ Sealing irregular gaps
- ✓ BS 476 Part 20:22 2HR*

* for guidance only, please refer to our technical department for test evidence.

Code	Description	Fire Rated	Size (ml)	Qty
FRFOAM	FR Expanding Foam	2 Hr*	750	1+

Intumescent Mastic



This adaptable intumescent mastic carries a 4 hour test report and is perfect for sealing irregular gaps behind frames etc. It comes in a standard 310ml cartridge suitable for use with a skeleton gun. The material is water based and therefore suitable for dry applications only.

Applications include:

- ✓ Sealing around doors and screens
- ✓ Backfilling around non combustible service penetrations
- ✓ Sealing irregular gaps
- ✓ BS 476 Part 20:22 4HR cavity protection*

* for guidance only, please refer to our technical department for test evidence.

Code	Description	Colour	Size (ml)	Qty/Box
INTW	Intumescent Mastic	White	310	25